

Printing Date 02/12/2017 Revision Number 1 Revision Date 02/12/2017

1 Identification

- · Product identifier
- · Trade name: MP54750, MP54750BK, MP54750GR Part B (Catalyst/Hardener)
- · Relevant identified uses of the substance or mixture. Curing Agent
- · Application of the substance / the mixture Hardener
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Adhesive Systems, Inc.

A Division of Royal Adhesives & Sealants, LLC

9411 Corsair Road Frankfort, Illinois 60423 Phone Number: 800-552-0299

- · Information department: Environment protection department.
- · Emergency telephone number:

ChemTrec: Day or Night within USA and Canada: 1-800-424-9300. Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

2 Hazard(s) identification

· Classification of the substance or mixture



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS05

GHS07

- · Signal word Danger
- · Hazard statements

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

· Precautionary statements

Do not breathe dusts or mists.

Wear protective gloves/protective clothing/eye protection/face protection.

Wash thoroughly after handling.

(Contd. on page 2)

Printing Date 02/12/2017 Revision Number 1 Revision Date 02/12/2017

Trade name: MP54750, MP54750BK, MP54750GR Part B (Catalyst/Hardener)

(Contd. of page 1)

Contaminated work clothing must not be allowed out of the workplace.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a POISON CENTER/doctor.

Specific treatment (see on this label).

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Wash contaminated clothing before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If swallowed: Rinse mouth. Do NOT induce vomiting.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Adhesive
- · Hazardous components:

112-24-3 3,6-diazaoctanethylenediamin

5-20%

4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for 20 minutes under running water. Call a Doctor immediately.
- · After swallowing:

Rinse mouth with water.

Do not induce vomiting; immediately call for medical help.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

Printing Date 02/12/2017 Revision Number 1 Revision Date 02/12/2017

Trade name: MP54750, MP54750BK, MP54750GR Part B (Catalyst/Hardener)

(Contd. of page 2)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Use fire fighting measures that suit the environment.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters

Firefighters use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

· Protective equipment: Protective clothing and respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste in accordance with federal state and local regulations.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

<i>PAC-1:</i>		1
	Polyamide	30 mg/m.
112-24-3	3,6-diazaoctanethylenediamin	<i>3 ppm</i>
PAC-2:		
	Polyamide	330 mg/m.
112-24-3	3,6-diazaoctanethylenediamin	14 ppm
<i>PAC-3:</i>		
	Polyamide	2,000 mg/m
112-24-3	3,6-diazaoctanethylenediamin	83 ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Open and handle receptacle with care.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires: No special measures required.

(Contd. on page 4)

Printing Date 02/12/2017 Revision Number 1 Revision Date 02/12/2017

Trade name: MP54750, MP54750BK, MP54750GR Part B (Catalyst/Hardener)

(Contd. of page 3)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location away from direct heat.
- Information about storage in one common storage facility: Store away from oxidizing agents.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

112-24-3 3,6-diazaoctanethylenediamin

WEEL Long-term value: 6 mg/m³, 1 ppm Skin

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment (see listings below)
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Nitrile rubber, NBR

Chloroprene rubber, CR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

Safety glasses with side shields.

Use full face shield over protective eye wear when there is a risk of a splash.

(Contd. on page 5)

Printing Date 02/12/2017 Revision Number 1 Revision Date 02/12/2017

Trade name: MP54750, MP54750BK, MP54750GR Part B (Catalyst/Hardener)

· Body protection: Protective work clothing

(Contd. of page 4)

	-1	
Information on basic physical and	chemical properties	
· General Information · Appearance:		
Form:	Liquid	
Color:	Amber	
· Odor:	Characteristic	
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
Melting point:	Undetermined.	
Boiling point:	204 °C (399 °F)	
· Flash point:	110 °C (230 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	335 °C (635 °F)	
Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
· Flammable limits:		
Lower:	Not determined	
Upper:	Not determined	
· Vapor pressure:	Not determined.	
· Specific gravity:	Not Determined	
· Relative density	Not determined.	
· Vapor density	1	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Slightly soluble.	
· Partition coefficient (n-octanol/wat	ter): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	0.0 %	
VOC (Per EPA 24)	=<1% mixed with Part A resin	
Solids content:	Not available	
· Other information	No further relevant information available.	

USA ·

Printing Date 02/12/2017 Revision Number 1 Revision Date 02/12/2017

Trade name: MP54750, MP54750BK, MP54750GR Part B (Catalyst/Hardener)

(Contd. of page 5)

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid Avoid high temperatures. Avoid freezing.
- · Incompatible materials:

Reacts with oxidizing agents.

Reacts with amines.

Reacts with acids.

chlorine

· Hazardous decomposition products:

Carbon monoxide

Carbon dioxide

Ammonia

Amines

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

112-24-3 3,6-diazaoctanethylenediamin

Oral LD50 2500 mg/kg (rat)
Dermal LD50 805 mg/kg (rabbit)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye:

Causes serious eye damage

Vapors may be irritating to the eyes.

- · Sensitization: Skin Contact Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.

(Contd. on page 7)

Printing Date 02/12/2017 Revision Number 1 Revision Date 02/12/2017

Trade name: MP54750, MP54750BK, MP54750GR Part B (Catalyst/Hardener)

(Contd. of page 6)

- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes: At present there are no ecotoxicological assessments.
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Must be specially treated adhering to official regulations.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

· UN-Number · DOT, ADN, IMDG, IATA	not regulated
· UN proper shipping name · DOT, ADN, IMDG, IATA	not regulated
· Transport hazard class(es)	
· DOT, ADN, IMDG, IATA · Class	not regulated
· Packing group · DOT, IMDG, IATA	not regulated
· Environmental hazards: · Marine pollutant:	Yes
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex L MARPOL73/78 and the IBC Code	I of Not applicable.
· Transport/Additional information:	The above DOT information applies to non-bulk containers. Not regulated by D.O.T. if in a container of 119 gallon capacity o less.
· UN ''Model Regulation'':	not regulated

-USA

(Contd. on page 8)

Printing Date 02/12/2017 Revision Number 1 Revision Date 02/12/2017

Trade name: MP54750, MP54750BK, MP54750GR Part B (Catalyst/Hardener)

(Contd. of page 7)

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· (DSL) Canada Dosmestic Substance List

All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements.

- · New Jersey Right-to-Know List:
- 112-24-3 3,6-diazaoctanethylenediamin
- · New Jersey Special Hazardous Substance List:

112-24-3 3,6-diazaoctanethylenediamin

CO

- · Pennsylvania Right-to-Know List:
- 112-24-3 3,6-diazaoctanethylenediamin
- · Pennsylvania Special Hazardous Substance List:

None of the ingredients is listed.

- · Cancerogenity categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients listed.

· MAK (German Maximum Workplace Concentration)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · National regulations:
- · Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.

(Contd. on page 9)

Printing Date 02/12/2017 Revision Number 1 Revision Date 02/12/2017

Trade name: MP54750, MP54750BK, MP54750GR Part B (Catalyst/Hardener)

(Contd. of page 8)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Royal Adhesives & Sealants makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Royal Adhesives & Sealants or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

- · Department issuing SDS: Environment protection department.
- · Creation Date: 02/12/2017
- · Date of preparation / last revision 02/12/2017 / -
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

 ${\it HMIS: Hazardous\ Materials\ Identification\ System\ (USA)}$

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health TLV: Threshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Skin Corr. 1B: Skin corrosion/irritation – Category 1B Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

USA